

<b>ELISALIVE2 Camera Specifications</b>		
<b>Camera</b>	Image Sensor:	1/3" Progressive Scan CMOS
	Min. Illumination:	0.01Lux @ (F1.2, AGC ON),0 Lux with IR
	Shutter time:	1/25(1/30) s to 1/100,000 s
	Lens:	2.8mm@ F2.0 Angle of view: 92.5°
	Lens Mount:	M12
	Day& Night:	IR cut filter with auto switch
	Wide Dynamic Range:	Digital WDR
	Digital noise reduction:	3D DNR
<b>Compression Standard</b>	Video Compression:	H.264
	Bit Rate:	32 Kbps ~ 16 Mbps
	Audio Compression:	AAC
	Dual Stream:	Yes
<b>Image</b>	Max. Image Resolution:	1280x720
	Frame Rate:	10-20 fps
<b>Network</b>	Network Storage:	Elisa Live cloud
	Alarm Trigger:	True motion detection by PIR
	Security:	HTTPS, encryption
<b>Interface</b>	Audio:	Internal Microphone
	Communication Interface:	1 RJ45 10M / 100M ethernet interface
	Reset Button:	Yes
<b>Wi-Fi Specification (-W)</b>	Wireless Standards:	IEEE802.11b, 802.11g, 802.11n
	Frequency Range:	2.4 GHz ~ 2.4835 GHz
	Channel Bandwidth:	20/40MHz Support
	Modulation Mode:	802.11b: CCK, QPSK, BPSK 802.11g/n: OFDM
	Security:	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
	Transmit Power:	11b: 17±1.5dBm @ 11Mbps 11g: 14±1.5dBm @ 54Mbps 11n: 12.5±1.5dBm
	Receive Sensitivity:	11b: -90dBm @ 11Mbps (Typical) 11g: -75dBm @ 54Mbps (Typical) 11n: -74dBm (Typical)
	Transmission Rate:	11b: 11Mbps 11g: 54Mbps 11n: up to 150Mbps
Wireless Range:	Outdoor: 200m, Indoor: 50m(depend on environment)	
<b>General</b>	Operating Conditions:	Indoor use only: -30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
	Power Supply:	12 VDC ± 10%, PoE (802.3af)
	Power Consumption:	5W MAX
	IR Range:	10 meters
	PIR:	Angle of detection: 80° Detection range: 10 meters
	Dimensions:	66×91.5×131.3(2.60"×3.60" ×5.17")
	Weight:	400g(0.88lbs)